



THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF THE SSC CONTROLS COMPANY AND IS NOT TO BE USED, REPRODUCED, OR DISCLOSED WITHOUT THE EXPRESS WRITTEN PERMISSION OF THE SSC CONTROLS COMPANY.








-BUMPER FEET AND Ø.220 MOUNTING HOLES (4 PLACES)





ENCLOSURE RATING: UL/CSA/NEMA ENCLOSURE TYPE 1 IEC 60529 IP 21

WEIGHT: 10.2 LB (4.6 KG)

## NOTES:

ALL DIMENSIONS ARE FOR REFERENCE ONLY.
BUMPER FEET ARE OPTIONAL (CAN BE REMOVED).
GUARD MATERIAL IS POWDER-PAINTED 12-GAUGE STEEL.

THIS MODEL SHOWS THE DUAL GUARD FOR THE DF-SERIES (ONE CABLE FOR BOTH SWITCHES).

EXAMPLE SHOWN: DF200-DG

## The SSC Controls Company

8909 EAST AVENUE MENTOR, OHIO, USA 44060

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES AND TOLERANCES ARE AS FOLLOWS

FOR 2 DECIMAL PLACES: ± .02 FOR 3 DECIMAL PLACES: ± .002 FOR ANGLES: ± .5 OF A DEGREE

	DRAWING INFORMATION	
/S:	DRAWN BY:	BAM
	CHECKED BY:	JEM
	DATE:	6/24/11
	SCALE:	NONE

## DUAL GUARD FOR DF-SERIES EXTERIOR DIMENSIONS

Drawing Number:

N/A