



THE SSC CONTROLS COMPANY

THE FOOT SWITCH EXPERTS®

Product Information Sheet

B-Series Foot Switches with Guards

The B-Series with Guards provide a tough powder-painted steel cover for any B-Series foot switch. The package includes the foot switch enclosed in a durable 12-gauge steel guard. The guard provides a comfortable housing in which to locate the foot, as well as protect the switch from debris.

Design features:

- Adds protection from debris and accidental actuation.
- Provides a secure location in which to position the foot.
- Tough, durable 12-gauge steel guard.
- Bolt-down holes included in the base.
- Includes non-skid rubber bumper feet.
- Available in any combination of B850 or B950 foot switches (standard models listed below).

Quality features:

- Designed and manufactured under a quality system certified to ISO 9001 requirements.
- Includes 1-year warranty.
- Made in USA of imported and domestic components.



Single Guard

Dimensions, L x W x H: 6.0" x 6.0" x 5.5"

Weight: 4 pounds

Finish: powder paint, safety orange




Dual Guard

Dimensions, L x W x H: 10.3" x 6.0" x 5.6"

Weight: 8 pounds

Finish: powder paint, safety orange

| Model | Action | Electrical Rating, per Switch | Cert. |
|--|-----------|--|---|
| B850-1501-G | Momentary | 15 A, 1/2 HP, 125 VAC, wired normally open; includes cable with piggyback plug for wall outlet |  |
| B850-1502-G | Momentary | 15 A, 1/2 HP, 125 / 250 VAC, wired normally open; includes cable with leads | |
| Note: Can add any single B850 unit to a single guard. For the Dual Guard, add "-DG" to the end of the model number. Add unit on left (when viewed from front) to first part of model number, and add unit on right to second part of model number (Example: B950/B850-1502-DG). If both units are the same, list only that model number followed by "-DG." | | | |



Warning: To avoid personal injury, do not use foot switches on machinery lacking effective point-of-operation safeguards. Disconnect input power before installation or maintenance.

The SSC Controls Company
8909 East Avenue Mentor, Ohio 44060
Phone: 440 205-1600 Fax: 440 205-1700