

# THE SSC CONTROLS COMPANY

THE FOOT SWITCH EXPERTS®

## **Product Information Sheet**

## **DF-Series Dual Foot Switch (Medium-Duty)**

The DF-Series Dual Foot Switch allows the combination of any two F-Series foot switches on a dual base.


### **Design features:**

- Combines two F-Series foot switches on a single base.
- Sleek rounded design with a welded steel center divider.
- One cable exit point with connector tube to route wiring from one side to the other (for most models).
- Cable cord grip is included (fits up to .60" diameter cable).
- Powder-painted black finish with bottom bumper feet.
- Four exterior mounting holes for bolt-down option.

#### **Quality features:**

- ISO 9001-certified quality system.
- Includes a 1-year warranty on parts and labor.
- Made in USA of imported and domestic components.





Weight: 4.7 pounds Finish: powder paint

Enclosure ratings: CSA Type 1; IP-20





**Warning:** To avoid personal injury, do not use foot switches on machinery lacking effective point-of-operation safeguards. Disconnect input power before installation or maintenance.

Model	Action	Electrical Rating, Each Side
DF200	Momentary	15 A, 1/2 HP, 125/250 VAC; 0.1 A, 125 VDC; SPDT
DF202	Momentary	15 A, 1/2 HP, 125/250 VAC; 0.1 A, 125 VDC; DPDT
DF300	Maintained	20 A, 125 VAC; 10 A, 250 VAC; SPST
DF500	Momentary	20 A, 125/250 VAC; 1 HP, 125 VAC; 2 HP, 250 VAC; .5 A, 125 VDC; .25 A, 250 VDC; 10 A, 125 VAC "L"; SPDT
DF200-1302	Momentary	Comes pre-wired with 16/4 cable; 13 A, 1/2 HP, 125/250 VAC

Note 1: See F-Series Product Information Sheet for complete details about F-Series models.

Note 2: Momentary action – press and hold to turn on, release to turn off (like a car horn). Maintained action – press once to turn on, press again to turn off (like a light switch).

Note 3: To add a 12-gauge steel guard in safety orange color, add "-DG" to the end of the model number. Example: DF200-DG

Custom models are available. See our website under the "Build Your Own F-Series Dual-Pedal Foot Switch (DF)" product page.

The SSC Controls Company 8909 East Avenue Mentor, Ohio 44060 Phone: 440 205-1600 Fax: 440 205-1700

