



THE SSC CONTROLS COMPANY

THE FOOT SWITCH EXPERTS®

Product Information Sheet

DG500 Dual Foot Switch (G-Series Two Pedal)

The DG500 connects any two G-Series foot switches onto a single platform. The unit consists of a rugged steel base with bumper feet. One cable exits the back of each foot switch. The handle has an easy-grip ball knob that makes it easy to lift or move around the unit without having to bend down (handle can be removed if not needed).



Design features:

- Can be equipped with any combination of G-Series foot switches.
- Tough steel base with durable bumper feet.
- Available with standard guard or "-OC" option.

Quality features:

- Quality system certified to ISO 9001 requirements.
- Includes a 1-year warranty on parts and labor.
- Made in USA.

Dimensions, L x W x H: 12.2" x 10.5" x 6.3"
(25" H w/ handle)

Weight (DG500-MO): 16 pounds typical

Finish: Safety Orange

Warning: To avoid personal injury, do not use foot switches on machinery lacking effective point-of-operation safeguards. Disconnect input power before installation or maintenance.



Dual Base with "-OC" guard option.

Model	Description
DG500	The DG500 can be equipped with any combination of G-Series foot switches. See naming convention below to specify the model.
"-OC" guard option	Same as above, but with no center divider between the two foot switches. See picture above. Specify with "-OC" at the end of the model number. Front Gate (-GT) option is not available on this model. Note: This model is not UL marked.

Naming convention: DG50X-XX/G50X-XX (first unit after the "D" is the left-side unit; second is the right side). If both units are the same, list only one. For example, a unit with two G500-MO foot switches mounted on the platform is model number DG500-MO. A unit with one G500-MO on the left side (when viewed from front) and one G502-MA on the right side is DG500-MO/G502-MA.

The SSC Controls Company
8909 East Avenue Mentor, Ohio 44060
Phone: 440 205-1600 Fax: 440 205-1700